Application:

Conduit outlet bodies are installed in conduit systems to:
- act as pull outlets for conductors being installed
- provide openings for making splices and taps in conductors
- act as mounting outlets for lighting fixtures and wiring devices
- connect conduit sections
- provide taps for branch conduit runs
- make 90° bends in conduit runs
- provide for access to conductors for maintenance and future system changes

Features:

Conduit Outlet Bodies

- Form 7 Condulet outlet bodies approach conduit in size for neat, compact installations.
- Form 8 and Mark 9 bodies provide more room for heavier conductors
- Many shapes and sizes are available for rigid threaded conduit – see complete listings on page 6.
- Conduit hubs have tapered threads and feature integral bushings for protection of wire insulation.
- Form 7 has exclusive snaptight and wedge-nut cover attachment to provide clear, unobstructed cover opening.
- Built-in rollers on all Form 5 1¼″ to 4″ C and LB bodies to facilitate wire pulling.
- Series 5 bodies available in optional configuration with set screws on hubs for EMT conduit (add suffix -MT to catalog number).

Gaskets

Solid gaskets:
- are used with blank covers
- for Mark 9 and Form 5, can be converted to open type gaskets by tearing out center section along scored lines – ½″ to 2″ sizes
- for Form 7 are used with all covers

Open gaskets:
- for Form 8 – ½″ to 4″ sizes
- for Mark 9 – 2½″ to 4″ sizes

Blank Covers

Stainless steel cover screws are standard on Form 7, Form 8, Mark 9, Series 5 and Form 5 covers.
- Form 7

Wedge nut design facilitates installation and removal. Nuts are held captive in cover. Covers can be used with or without gaskets.

SNAPTIGHT™ Form 7 Covers with integral sealing gaskets are installed without the use of screws, reducing installation time and costs. Covers are reusable.
- Form 8

Two cover screws provided on all sizes to provide tight cover and gasket assembly. *Feraloy* iron alloy covers have dome shapes for added strength and extra wiring room.
- Mark 9

Self-retaining cover screws.

Standard Materials:

- Form 7, Form 8 outlet bodies – *Feraloy* iron alloy
- Mark 9 outlet bodies – copper-free aluminum
- Form 5 – malleable iron
- Series 5 – die cast aluminum

Standard Finishes:

- Form 7, Form 8 outlet bodies – electrogalvanized with aluminum acrylic paint
- Mark 9 outlet bodies – natural
- Form 5 – electrogalvanized with aluminum acrylic paint
- Series 5 – aluminum acrylic paint

Options:

Description	Suffix to be Added to Cat. #
Form 7 body and cover only:	
Copper-free aluminum.	SA
Corro-free™ epoxy powder coat.	add suffix S752

- Series 5 in an EMT version with set screws on all hubs .... add suffix -MT
- Series 5 pre-packaged with neoprene gasket and cover .... add suffix -CGN

Certifications and Compliances:

Outlet Bodies –
- UL Standard: 514B
- Fed. Spec.: W-C-586D
- CSA Standard 22.2 No. 18

Size comparison of 1½″ Form 7, Mark 9, Form 8, and Mogul bodies. Round backs on Form 7 and Mogul; flat backs on Form 8 and Mark 9. The round back conduit body is a registered trademark of Cooper Industries, Inc.
- Raintight (when installed with cover and gasket)

Form 7 ®

Mark 9

Form 8

Mogul ®

 Copyright® 2006 Cooper Crouse-Hinds