# Product data sheet
## Characteristics

# XACA2014
## Pendant control station, plastic, yellow pistol grip, 2 push buttons + 1 emergency stop

Product availability : Non-Stock - Not normally stocked in distribution facility

## Main

| | |
|---|---|
| Range of product | Harmony XAC |
| Product or component type | Pendant control station |
| Device short name | XACA pistol grip |

## Complementary

| | |
|---|---|
| Control station type | Double insulated |
| Enclosure material | Polypropylene |
| Control type | Intuitive |
| Electrical circuit type | Control circuit |
| Enclosure type | Complete ready for use |
| Control station application | Control of single speed hoist motor |
| Control station composition | 2 push-buttons + 1 emergency stop |
| Control button type | First push-button 1 NO raise, slow<br>Second push-button 1 NO lower, slow<br>Emergency stop push-button Ø 30 mm 1 NC trigger action |
| Product compatibility | ZB2BE101 for each direction<br>ZB2BE102 for emergency stop |
| Mechanical interlocking | With mechanical interlocking |
| Control station colour | Yellow |
| Connections - terminals | Screw clamp terminals, 1 x 2.5 mm² with or without cable end<br>Screw clamp terminals, 2 x 1.5 mm² with or without cable end |
| Standards | EN/ISO 13850: 2006<br>EN/IEC 60204-32<br>EN/IEC 60947-5-1<br>CSA C22.2 No 14<br>EN/IEC 60947-5-5<br>UL 508 |
| Product certifications | UL |

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| | CSA |
| Protective treatment | TH |
| Ambient air temperature for operation | -13…158 °F (-25…70 °C) |
| Ambient air temperature for storage | -40…158 °F (-40…70 °C) |
| Vibration resistance | 15 gn 10…500 Hz)IEC 60068-2-6 |
| Shock resistance | 100 gn IEC 60068-2-27 |
| Overvoltage category | Class II IEC 61140 |
| IP degree of protection | IP65 IEC 60529 |
| IK degree of protection | IK08 EN 50102 |
| Mechanical durability | 1000000 cycles |
| Cable entry | Rubber sleeve with stepped entry 7…15 mm |
| Contact code designation | A600 AC-15, Ue = 240 V, Ie = 3 A IEC 60947-5-1 appendix A<br>A600 AC-15, Ue = 600 V, Ie = 1.2 A IEC 60947-5-1 appendix A<br>Q600 DC-13, Ue = 250 V, Ie = 0.27 A IEC 60947-5-1 appendix A<br>Q600 DC-13, Ue = 600 V, Ie = 0.1 A IEC 60947-5-1 appendix A |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 600 V 3)IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 6 kV IEC 60947-1 |
| Contact operation | Slow-break |
| Maximum resistance across terminals | 25 MOhm |
| Operating force | 13…15 N |
| Short-circuit protection | 10 A fuse protection cartridge gG |
| Rated operational power in W | 40 W DC-13 1000000 cycles 60 cyc/mn 120 V 0.5 inductive IEC 60947-5-1 appendix C<br>48 W DC-13 1000000 cycles 60 cyc/mn 48 V 0.5 inductive IEC 60947-5-1 appendix C<br>65 W DC-13 1000000 cycles 60 cyc/mn 24 V 0.5 inductive IEC 60947-5-1 appendix C |
| Terminals description ISO n°1 | (13-14)NO |
| Terminals description ISO n°2 | (11-12)NC |
| Terminal identifier | (13-14)NO<br>(11-12)NC |
| Net Weight | 0.68 lb(US) (0.31 kg) |

## Ordering and shipping details

| | |
|---|---|
| Category | 22473 - PUSHBUTTON, PENDANTS |
| Discount Schedule | CS2 |
| GTIN | 00785901171522 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.22 lb(US) (0.10 kg) |
| Returnability | No |
| Country of origin | FR |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.97 in (5 cm) |
| Package 1 width | 4.33 in (11 cm) |
| Package 1 Length | 11.61 in (29.5 cm) |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |

| | |
|---|---|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)<br>EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |